



X-Loupe® MightyGetter-P4 Specification

Camera	
Compatible Camera Types	Canon IXUS 870 IS or latest model* (*If the specified Canon camera phased out, Lumos will replace the Canon cameras with same level or higher level cameras)
Detailed Camera Specification	Please refer to Camera Manual
Exchangeable Objective Lens	
Objective Lenses	30x Objective Lens for collecting Dactylogram purpose
Lens Material	Schott® lead-free Option glass MgF2 High-Efficient Anti-Reflection Coating
Field of View	23.5*17.5mm~27.5*20mm adjustable
Resolution (by USAF 1951 Target)	28.5 lp / mm
Illumination	White-light LED : 9pcs
Module	
Display	Battery Status
Battery	820Ah SANYO Li-ion battery core, Canon NB-5L compatible
Current Consumption	Max. 540mA
Battery Duration	3 Hrs.
Battery Charging	Use the attached charger only 8 hrs for first time; 3 hrs for general usage.
Max. Dimension (mm)	150(L, with 300X lens) x 108 (w) x 65 (H)
Weight of Microscopic Lens Module	Less than 310g (Battery included)
Weight with DSC*	Less than 500g(Battery included)
Operation Environment	0-40°C / 32-104°F

* DSC : Digital Still Camera

7th floor, No.8, Wanhe St., Wenshan District,
116 Taipei City, Taiwan, R.O.C.
TEL:886-2-2230-1168 FAX:886-2-2239-2112

e-mail:service@lumos.com.tw

http://www.x-loupe.com http://www.lumos.com.tw


Lumos Technology Co. Ltd.