

Handheld Micro Shoot Series

HMS-M43, a handheld microscope with blue light

As the microscope lens and control unit mounted, the camera quickly turn into a handheld microscope.

Space-saving for operation, time-saving for assembly.

Ring-shaped excitation light sources confined in lens barrel, keep a safe shooting, avoid the effect of background light.

Can be used for detection and photo-taking of the fluorophores.

(ex. GFP or fluorescence fingerprint)

Application area

- Aviation & Aerospace
- High-tech manufacturing
- Research & Education
- Antique Identification
- Printing, Counterfeit Detection

Or the need for fluorescence detection such as Life sciences, Forensic Science and other fields.



Features

- ⦿ *Allowing 0 cm working distance, can be totally stick close to the shooting object.*
- ⦿ *Lens magnification 60X / 120X, built-in White / blue dual light sources can be freely alternated.*
- ⦿ *Lighting come in 11 modes, can be different adjustment for varying objects surface to get the best results of shooting.*
- ⦿ *Freely adjustable light intensity, is dimmable from 1% to 100% with 5-step dimming modes.*

X-Loupe® Handheld Micro Shoot Series / HMS-M43 Specification

X-Core (Control unit)	
Function	Power ON, Off / Light Channel Switch / Lighting Modes Setting / Dimming Control
LCD Status Display	Battery check / Channel output / Lighting Modes / Lighting Intensity
Battery	Built-in SANYO® Rechargeable Li-ion Battery, 5200mAh
Charging method	via Power Adapter (packed separately) Input: AC 100~240V; Output: DC 5V / 2A NOTE: Only use the dedicated charger for charging
Charging Time	1st charge 8 hrs and subsequently charge around 4 hrs
Lasting Time (5200mAh)	10 hrs with default light intensity, 6 hrs with maximum intensity (5-step)
Body Material	ABS and PMMA, RoHS compliant
Dimension	88.3mm x 63.15mm x 54mm
Weight	< 200g
Operation Environment	0~40°C
Objective Lenses	
compatible with camera / lens	① OLYMPUS M.ZUIKO DIGITAL ED 60mm F2.8 Macro ② Panasonic DG Leica 45mm F2.8 Macro O.I.S
Camera / Specifications and Using	Please Refer to camera manual
Included Number of Objective Lens	2
Magnification Power	60X 120X
Lens Material	Schott® lead-free optical glass and OHARA composite spherical mirror, high transmittance and MgF ₂ AR coating Schott® lead-free aspheric optical glass, high transparency and MgF₂ AR coating
Field of View (By 1*1mm graph paper)	10.5 x 8.2 mm 6.8 x 5.5 mm
Resolution (by USAF 1951 Target)	64 lp / mm 114 lp / mm
Max. Dimension (mm)	41mm x 54mm 39 mm x 54 mm
Weight of Lens Barrel	125g 125g
Mounting Method for lens	Magnet mount
Channel & Light source	Channel W: White light Channel F: Blue light (or Custom wavelength)
LED Brand	White light: High power OSRAM LED Blue light: High power OSRAM, choose by wavelength
LED Number	16 (each channel x 8)
Dimming intensity	General intensity is dimmable from 1% to 100% with 5-step dimming modes Only in the charging status of power adapter can enable the Turbo mode (6-step)
Max. current on LED (6-step)	60 mA
Lighting Modes	11 modes: Full Ring light x 1 ▶ Half Ring light x 4 ▶ 1:2 Brightness Ratio x 4 ▶ Diagonal light x 2
Max. Current Consumption	White light (5000K) / 1330 mA Blue light (wavelength 470nm) / 650 mA
Adaptor ring components	①Adapter Ring (specified for use with M4/3); ②30mm (Glass) Filter; ③Lens Adapter Ring
Materiall	Aluminum Alloy, Optical Grade Glass, Acrylic, ABS, PC, RoHS compliant
Power cable length	30 cm
Operation Environment	0~40°C / 32~104°F

*We (Lumos Tech.) reserves the right to change the product appearance or specification. The contents of catalogs / manuals are subject to change without prior notice.

Distributor



7th floor, No.8, Wanhe St., Wenshan District,
11653 Taipei City, Taiwan, R.O.C.
TEL:886-2-2230-1168 FAX:886-2-2239-2112
e-mail:contact@lumos.com.tw
www.x-loupe.com

D HMS-M43E
041322



Lumos Technology Co. Ltd.